hand a second	
ES ENVIRONMENTAL PROTECTION I 726 Minnesota Avenue KANSAS CITY KS 66101 SIMILE REQUEST AND COVER	
PLEASE PRINT IN BLACK INK ONLY	
Pauling	
1089 1180 1	
;+4	
2888 MAIL CODE	
NUMBER OF PAGES T	TO INCLUDE THIS COVER SHEET
Please number all pages AATION FOR SENDING FACSIMILE M	ESSAGES
FACSIMILE NUMBER	VERIFICATION NUMBER
FTS: 757-2845(auto) Comm: (913)236-2845	FTS: 757-2827, Ext 211 Comm: (913)236-2827, Ext 211
	Please number all pages Pacsimile Mumber Please Print in Black ink Only Mul Code Number of Pages Attion for Sending Facsimile Mumber Facsimile Number Facsimile Number Facsimile Number Facsimile Number Facsimile Number

R00105800 RCRA RECORDS CENTER

PAGE T OF A PAGES

Monsanto

If tetrachloroethylene is to remain a POHC, then the Modified Method 5 (MM5) Sampling Train must be used simultaneously with the VOST. The VOST is designed for compounds with boiling points between 30°C and 100°C, while the MM5 Train is designed for compounds with boiling points greater than 100°C.

Although performance audits of the VOST have shown that acceptable ranges of accuracy can be achieved for tetrachloro-ethylene, we have seen no data which suggests it is more effective the MM5 sampling train for tetrachloroethylene.

Furthermore, sampling both trains will enable Monsanto to run a complete scan of both volatile and semi-volatile compounds, this will provide valuable information concerning the formation of products of incomplete combustion (PICs). This information will be extremely important in setting incinerator permit operating conditions. As of yet, we have no information concerning the carbon monoxide (CO) emissions from the unit, and therefore, no indication of operating combustion efficiency. It is possible for an incinerator to operate at poor combustion efficiencies (high CO) and still pass the required destruction and removal efficiency (DRE). In these cases PIC emissions can pose a significant threat to human health and the environment. Given Monsanto's urban location, any potential threat to human health is magnified.

The absence of an indication of semi-volatile FIC emission data, coupled with poor combustion efficiency, may result in Monsanto conducting a second trial burn even if DREs are met.

Performance
Both the VOST and the MM5 have been evaluated
for tetrachloroethylene. Both trains are adequate.
However, the MM5 is probably more accurate.

- CO cut off



which